

TECHNICAL DATA SHEET

Eurovent **DIFFUBAND SK2**

Sealing tape with low Sd coefficient for insulation of the connection for the outside. Made of highly vapour-permeable membrane fully coated with an adhesive layer on one side and an adhesive strip on the other side that provides optimal performance and makes plastering and final processing easier.



PARAMETER	UNIT	VALUE
Water tightness		W1
Vapour permeability	[Sd]	0,3 (±0,02)
Flammability class	[mm]	E
Adhesive	[mb]	Acrylate dispersion, solvent free EC1 ^{PLUS}
Adhesive Coating	[mm]	230 g/m ²
Temperature resistance	[g/m ²]	-40 °C to +80 °C
Carrier Material	[°C]	1 layer pp nonwoven
UV Resistance	[°C]	4 months
Shelf life		1 year
Available widths		70, 100, 150 mm x 25 m
Package – quantity per box (per pallet)		1 rolls (416); 1 rolls (320); 4 rolls (192)
Application temperature		From - 5°C, ideal processing temp. + 5 °C to + 35°C
Storage		in a dry place at a temperature of + 15 °C to + 25°C

Advantages:

- Vapour insulating • flexible and easy to install
- Wind insulation • Allows moisture drainage from joints
- Very low emission EMICODE® EC1^{PLUS}

Eurovent **DIFFUBAND SK2**

Application:

For the installation of windows and doors in a way that ensures their tightness for many years. Dedicated for the insulation of connections outside the building. The product is self-adhesive on the entire surface which makes easy installation of the foil. Additionally, it contains an adhesive stripe on the top side which facilitates fastening of the tape to the wall and eliminates the need of using additional adhesive.



Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 05/2019