

Corotop Vapo

Fixing tape for vapour barriers and corners

Single-sided self-adhesive tape made of polyethylene film and adhesive based on acrylic dispersion, reinforced with polyester fiber. Particularly dedicated to bonding vapor-insulating films. Thanks to the split liner, ideal for all processing of installation passages, corners or edges. The tape meets the EMICODE® EC1PLUS premium emission class.



Advantages

- ✓ high bonding strength
- ✓ with splitted liner
- ✓ meets EMICODE® EC1PLUS premium emission class
- ✓ easier processing of edges and corners

Application

- ✓ ideal for joining edges and corners
- ✓ for polypropylene and polyethylene vapour-barriers
- ✓ for connecting foil with plastics, concrete, wood and metal
- ✓ for use inside building structures



Characteristics

Material	LDPE, polyester mesh, acrylic adhesive	Peel strength of joints	≥ 35 N/25mm
Colour	green/white printing	Sd value	ca.30m
Length	25 m	Temperature of application	from +5°C
Width	60 mm	Temperature resistance	From -30°C to +100°C

Installation

1. Glued surfaces must be dry, free of dust and oil
2. The product should be mounted without tensioning.
3. After laying the tape on the target Surface, press the tape with a spatula or roofing roller.
4. The recommended temperature of application must be observed.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage. Storage at 15-25 °C with rH 40 - 60%.

Packaging

Quantity per box (pcs.):	5
Quantity on a pallet (box/pcs.):	175/875

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.